Environmental Impact Assessment and Environmental Risk Assessment: Review of Concepts, Steps and Significance

*Okeukwu, E,K., Okeke, O. C, Irefin, M.O, Ezeala, H.I, and Amadi, C.C,

Department of Geology, Federal University of Technology, Owerri, Nigeria. Corresponding authors email *ezinnekindness2@gmail.com

D.O.I: 10.56201/ijgem.v9.no2.2023.pg25.51

ABSTRACT

Environmental Impact Assessment is an assessment of the possible positive or negative impact a proposed project will have on the environment, considering the natural, social and economic aspects. while Environmental risk assessment assess the likelihood of your business activities or operation causing harm to the environment, it involves the process of assessing the risk human activities may have on the environment, the environment here includes human beings (health hazards impact) and ecology (impacts on fauna and flora). This includes describing potential hazards and impacts before taking precautions to reduce the associated risks. . It uses similar techniques to the health and safety risk assessment your business already has to perform. A risk assessment typically involves many steps and forms the backbone of the overall risk management plan. A risk analysis is one of those steps—the one in which you determine the defining characteristics of each risk and assign each a score based on your findings. The major differences between environmental impact assessment and environmental risk assessment includes the following: While environmental impact assessment is a broad field that includes all activities that attempt to analyze and evaluate the effects of human and related actions on the environment, risk assessment are generally concerned with the relatively well-defined regulatory problems and employs formal quantitative analysis of the potential risk. This paper highlights the concept of environmental impact assessment and environmental risk assessment, their steps and significance and gives the case histories of both environmental impact assessment and environmental risk assessment.

Keywords: risk assessment, health risk, environment, impact assessment, hazard

1.0 INTRODUCTION: CONCEPTS/DEFINITION AND SCOPE OF ENVIRONMENTAL IMPACT ASSESSMENT AND ENVIRONMENTAL RISK ASSESSMENT

An environmental impact assessment (EIA) is an assessment of the possible positive or negative impact that a proposed project may have on the environment, considering natural, social and economic aspects. In this context, the term "environmental impact assessment" is usually used when applied to actual projects by individuals or companies and the term "strategic environmental assessment" (SEA) applies to policies, plans and programmes most often

IIARD – International Institute of Academic Research and Development

proposed by organs of state. (Mackinnon et al. 2018, Eccleston 2011). It is a tool of environmental management forming a part of project approval and decision making (Caves 2004). The International Association for Impact Assessment (IAIA) defines an environmental impact assessment as "the process of identifying, predicting, evaluating and mitigating the biophysical, social, and other relevant effects of development proposals prior to major decisions being taken and commitments made" (IAIA 2012). EIAs are unique in that they do not require adherence to a predetermined environmental outcome, but rather they require decision makers to account for environmental values in their decisions and to justify those decisions in light of detailed environmental studies and public comments on the potential environmental impacts (Holder 2004). However when special consideration is paid to the social effects of the project, environmental impact assessment (EIA) is often referred to as environmental and social impact assessment (ESIA). EIA typically involves technical evaluations that generally lead to objective decision making.

An environmental risk assessment (ERA) assess the likelihood of your business activity or operation causing harm to the environment. This includes describing potential hazards and impacts before taking precautions to reduce the associated risks. It uses similar techniques to the health and safety risk assessment your business already has to perform. A risk assessment typically involves manv and forms the backbone of the steps overall risk management plan. A risk analysis is one of those steps—the one in which you determine the defining characteristics of each risk and assign each a score based on your findings.

Risk assessments are used to characterize the nature and magnitude of health risks to humans (e.g., residents, workers, recreational visitors) and ecological receptors (e.g., birds, fish, wildlife) from chemical contaminants and other stressors, that may be present in the environment. While there are many definitions of the word risk, it is usually considered to be the chance of harmful effects to human health or to ecological systems resulting from exposure to an environmental stressor.

Definition of an Environmental Risk

Environmental risk can be defined as the "actual or potential threat of adverse effects on living organisms and the environment by effluents, emissions, wastes, resource depletion, etc., arising out of an organization's activities." Environmental exposures, whether physical, chemical, or biological, can induce an environmental risk.

Risk assessment determines possible mishaps, their likelihood and consequences, and the tolerances for such events (Rausand, 2013). The results of this process may be expressed in a quantitative or qualitative fashion. Risk assessment is an inherent part of a broader risk management strategy to help reduce any potential risk-related consequences (Rausand, 2013) (Manuele 2016).

Risk assessments can be done in individual cases, including in patient and physician interactions (Levi, R, 2018). In the narrow sense chemical risk assessment is the assessment of a health risk in response to environmental exposure (Varshavshy et al 2023).

A systematic review of patients and doctors from 2017 found that overstatement of benefits and understatement of risks occurred more often than the alternative (Hoffmann and Del Mar 2015).

A 2017 systematic review from the Cochrane collaboration suggested "well-documented decision aids" are helpful in reducing effects of such tendencies or biases (Stacey, et al 2017).

Risk assessment can also be made on a much larger systems theory scale, for example assessing the risks of an ecosystem or an interactively complex mechanical, electronic, nuclear, and biological system or a hurricane (a complex meteorological and geographical system). Systems may be defined as linear and nonlinear (or complex), where linear systems are predictable and relatively easy to understand given a change in input, and non-linear systems unpredictable when inputs are changed(Rausand, 2013) As such, risk assessments of non-linear/complex systems tend to be more challenging.

In the engineering of complex systems, sophisticated risk assessments are often made within safety engineering and reliability engineering when it concerns threats to life, natural environment, or machine functioning. The agriculture, nuclear, aerospace, oil, railroad, and military industries have a long history of dealing with risk assessment (Vamanu, et al 2016). Also, medical, hospital, social service. (Lacey, 2011). it also involves documentation of the risk assessment and its findings, implementation of mitigation methods, and review of the assessment (or risk management plan), coupled with updates when necessary. Sometimes risks can be deemed acceptable, meaning the risk "is understood and tolerated . Usually because the cost or difficulty of implementing an effective counter measure for the associated vulnerability exceeds the expectation of loss (Shirey, Benoit Mandelbrot distinguished between 2007) and "wild" risk and argued that risk assessment and risk management must be "mild" fundamentally different for the two types of risk (Mandel brot, et al 1988). The usefulness of quantitative risk assessment has been questioned, however. Barry Commoner, Brian Wynne and other critics have expressed concerns that risk assessment tends to be overly quantitative and reductive. For example, they argue that risk assessments ignore qualitative differences among risks. Some charge that assessments may drop out important non-quantifiable or inaccessible information, such as variations among the classes of people exposed to hazards, or social amplification (kasperson, et al 1988). Furthermore, (Commoner and O'Brien 2002) claim that quantitative approaches divert attention from precautionary or preventative measures. (Shraderfrechette and Westra, 1997). Others, like Nassim Nicholas Taleb consider risk managers little more than "blind users" of statistical tools and methods (Taleb 2008). At the individual level, identifying objectives and risks, weighing their importance, and creating plans, may be all that is necessary. At the strategic organisational level, more elaborate policies are necessary, specifying acceptable levels of risk, procedures to be followed within the organisation, priorities, and allocation of resources (Lock 2017)

Difference between Environmental Risk Assessment and Environmental Impact Assessment

The major differences between environmental impact assessment and environmental risk assessment includes the following: While environmental impact assessment is a broad field that includes all activities that attempt to analyze and evaluate the effects of human and related actions on the environment, risk assessment are generally concerned with the relatively well-defined regulatory problems and employs formal quantitative analysis of the potential risk.

2.0 STEPS/METHODS AND SIGNIFICANCE OF ENVIRONMENTAL IMPACT ASSESSMENT

2.1 Steps /Methods of Environmental Impact Assessment

Environmental impact assessment Methodology:

Whenever a new development project is planned which is likely to affect environmental quality, it is necessary to carry out EIA studies. The methodology that is typically followed for a standard EIA study involves the following:

1. The first step in EIA technique is to determine whether the project under consideration follows the jurisdiction of the relevant acts and regulations and if so, whether it is likely to create a significant environmental disruption.

2. If so, an EIA is undertaken and the environmental impact statement (EIS) is prepared.

3. In many countries, EIS is open to public scrutiny and is reviewed at public hearings.

4. Finally, a political decision is taken. The development project may be (i) accepted or (ii) accepted with amendments or (iii) an alternative proposal is accepted or (iv) rejected.

Environment Impact Assessment Process

In EIA system, there is a sequence of activities implemented in a project in logical manner termed as the EIA process.

Environmental impact assessment Process in Sequence of Application:

1. Stakeholder's Involvement:

Stakeholders' involvement occurs in various stages of EIA to ensure quality, efficiency and effectiveness.

2. Project Screening and Scoping:

(i) Determine necessity for EIA requirement.

- (ii) Describe various screening criteria.
- (iii) Scoping determines coverage or scope of EIA.

3. Project Design and Construction:

- (i) Type of project under consideration.
- (ii) Physical dimensions of the area being considered.
- (iii) Whether the resources will be used optically?

4. Project Operation:

- (i) What provisions have been made to check the safety equipment regularly?
- (ii) How will the hazardous waste products be handled?
- (iii) What are the contingency plans developed to cope up with the possible

5. Site Characteristics:

(i) Whether the site is susceptible to floods, earth quakes and other natural disasters?

(ii) Whether the terrain is creating problems in predicting ground water characteristics and air pollution etc.?

(iii) Whether the local environment is conductive for the success of the project?

6. Possible Environmental Impacts:

(i) What are the possible short-term and long-term environmental impacts from the projects during construction and after construction?

(ii) Who would be effected because of these impacts?

7. Mitigation Measures:

(i) Design system to avoid, reduce and minimize adverse impacts.

(ii) Enhance beneficial outcomes.

8. Monitoring and auditing measures:

(i) Identify impacts that require monitoring and auditing.

9. Socio-Economic Factors:

(i) Who are the expected gainers and losers by the projects?

(ii) Where are the expected trade-offs?

Objectives of EIA

The objectives of EIA include the following:

- (i) To identify, predict and evaluate the economic, environmental and social impact of development activities
- (ii) To provide information on the environmental consequences for decision making and
- (iii) To promote environmentally sound and sustainable development through the identification of appropriate alternatives and mitigation measures.

IIARD – International Institute of Academic Research and Development

2.2 Significance of the environmental impact assessment (EIA)

The significance of EIA is:

1) EIA is more than technical reports, it is a means to a larger intention - the protection and improvement of the environmental quality of life.

2) EIA is a procedure to identify and evaluate the effects of activities (mainly human) on the environment - natural and social.

3.0 STEPS/METHOD AND SIGNIFICANCE OF ENVIRONMENTAL RISK ASSESSMENT

3.1 steps/method of environmental risk assessment

Five Steps to Risk Assessment

Risk assessment process is usually broken down into three separate steps: risk identification, risk analysis, and risk evaluation.

Step 1: Identify the Hazards

Identify the hazards. Walk around your environment and look at what could reasonably be expected to cause harm. Ask your other people what they think. They may have noticed things that are not immediately obvious to you. Visit the HSE website. HSE publishes practical guidance on where hazards occur and how to control them about long-term hazards to health (eg high levels of noise or exposure to harmful substances) as well as safety hazards.

Step 2: Decide who might be harmed and how

Decide who might be harmed and how For each hazard you need to be clear about who might be harmed; it will help you identify the best way of managing the risk. That doesn't mean listing everyone by name, but rather identifying groups of people (eg 'people working in the storeroom' or 'passers-by'). Remember: some workers have particular requirements, eg new and young workers , migrant workers , new or expectant mothers and people with disabilities may be at particular risk.

Step 3: Evaluate the risks and decide on precautions

Evaluate the risks and decide on precautions. Having spotted the hazards, you then have to decide what to do about them. The law requires you to do everything 'reasonably practicable' to protect people from harm. You can work this out for yourself, but the easiest way is to compare what you are doing with good practice

Step 4: Record your findings and implement them

Record your findings and implement them. Putting the results of your risk assessment into practice will make a difference when looking after people and your fundraising event. Writing down the results of your risk assessment, and sharing them, encourages you to do this. When writing down your results, keep it simple, for example 'Tripping over rubbish: bins provided, staff instructed, weekly housekeeping checks'

Step 5: Review your risk assessment and update

Review your risk assessment and update if necessary. Things are likely to change between first conducting your risk assessment and your fundraising event. It makes sense therefore, to review what you are doing on an ongoing basis.

Classification of Environmental Risk Assessment

Environmental risk assessments typically fall into one of two:

- a. Human Health Assessment
- b. Ecological Assessment

Human Health Assessment

General human health

There are many resources that provide human health risk information:

The National Library of Medicine provides risk assessment and regulation information tools for a varied audience. (Risk assessment and regulation information from NLM 2013). These include:

- TOXNET (databases on toxicology, hazardous chemicals, environmental health, and toxic releases 2013),
- the Household Products Database (potential health effects of chemicals in over 10,000 common household products), (Household products Database 2013)
- TOXMAP (maps of the U.S. Environmental Protection Agency Superfund and Toxics Release Inventory data).

The United States Environmental Protection Agency provides basic information about environmental health risk assessments for the public for a wide variety of possible environmental exposures (Risk Assessment portal, EPA 2013)

The Environmental Protection Agency began actively using risk assessment methods to protect drinking water in the United States after the passage of the Safe Drinking Water Act of 1974. The law required the National Academy of Sciences to conduct a study on drinking water issues, and in its report, the NAS described some methodologies for doing risk assessments for chemicals that were suspected carcinogens, recommendations that top EPA officials have described as perhaps the study's most important part, (EPA Alumni association: senior EPA officials discuss early implementation of drinking water act of 1974).

Considering the increase in junk food and its toxicity, FDA required in 1973 that cancer-causing compounds must not be present in meat at concentrations that would cause a cancer risk greater than 1 in a million over a lifetime. The US Environmental Protection Agency provides extensive information about ecological and environmental risk assessments for the public via its risk assessment portal (Risk assessment EPA, 2013.) The Stockholm Convention on persistent organic pollutants (POPs) supports a qualitative risk framework for public health protection from chemicals that display environmental and biological persistence, bioaccumulation, toxicity

(PBT) and long range transport; most global chemicals that meet this criteria have been previously assessed quantitatively by national and international health agencies (szabo and Loccisano, 2012).

For non-cancer health effects, the terms reference dose (RfD) or reference concentration (RfC) are used to describe the safe level of exposure in a dichotomous fashion. Newer ways of communicating the risk is the probabilistic risk assessment (Nielsen etal 2023).

Even a human health risk assessment starts with a good plan. Before anything though there is a need to make judgments early when planning major risk assessments regarding the purpose, scope, and technical approaches that will be used. Typically risk assessors will ask the following questions:

- 1. Who/What/Where is at risk?
- Individual
- General population
- Life stages such as children, teenagers, pregnant/nursing women
- Population subgroups highly susceptible (for example, due to asthma, genetics, etc.) and/or highly exposed (for example, based on geographic area, gender, racial or ethnic group, or economic status)
- 2. What is the environmental hazard of concern?
- Chemicals (single or multiple/cumulative risk)
- Radiation
- Physical (dust, heat)
- Microbiological or biological
- Nutritional (for example, diet, fitness, or metabolic state)
- Socio-Economic (for example, access to health care)
- 3. Where do these environmental hazards come from?
- Point sources (for example, smoke or water discharge from a factory; contamination from a Superfund site)
- Non-point sources (for example, automobile exhaust; agricultural runoff)
- Natural sources
- 4. How does exposure occur?
- Pathways (recognizing that one or more may be involved)
- Air
- Surface Water
- Groundwater
- Soil

- Solid Waste
- Food
- Non-food consumer products, pharmaceuticals

Steps usually taken for Human Health Assessment

Step 1: Hazard identification:

Hazard identification is the first step of a human health risk assessment. Hazard Identification is the process of determining whether exposure to a stressor can cause an increase in the incidence of specific adverse health effects (e.g., cancer, birth defects). It is also whether the adverse health effect is likely to occur in humans. The objective of Step 1 is to identify the types of adverse health effects that can be caused by exposure to some agent in question, and to characterize the quality and weight of evidence supporting this identification.

Key Components of Hazard Identification

A wide variety of studies and analysis are used to support a hazard identification analysis. These studies include the following:

- i. Toxicokinetics
- ii. Toxicodynamics

Step 2: Dose-response assessment

Dose-response assessment is the second step of a human health risk assessment. A dose-response relationship describes how the likelihood and severity of adverse health effects (the responses) are related to the amount and condition of exposure to an agent (the dose provided). Although this webpage refers to the "dose-response" relationship, the same principles generally apply for studies where the exposure is to a concentration of the agent (e.g., airborne concentrations applied in inhalation exposure studies), and the resulting information is referred to as the "concentration-response" relationship.

Step 3: Exposure Assessment

Exposure assessment is the process of measuring or estimating the magnitude, frequency, and duration of human exposure to an agent in the environment, or estimating future exposures for an agent that has not yet been released. An exposure assessment includes some discussion of the size, nature, and types of human populations exposed to the agent, as well as discussion of the uncertainties in the above information.

Different Kinds of Doses. Exposure assessment considers both the exposure pathway (the course an agent takes from its source to the person(s) being contacted) as well as the exposure route (means of entry of the agent into the body). The exposure route is generally further described as intake (taken in through a body opening, e.g. as eating, drinking, or inhaling) or uptake (absorption through tissues, e.g. through the skin or eye).

Range of Exposure. For any specific agent or site, there is a range of exposures actually experienced by individuals. Some individuals may have a high degree of contact for an extended period (e.g. factory workers exposed to an agent on the job). Other individuals may have a lower degree of contact for a shorter period (e.g. exposure assessment requires consideration of a range of possible exposure levels. individuals using a recreational site downwind of the factory). EPA policy for exposure assessment requires consideration of a range of possible exposure levels.

Two common scenarios for possible exposure are "Central Tendency" and "High End". "Central Tendency" exposure is an estimate of the average experienced by the affected population, based on the amount of agent present in the environment and the frequency and duration of exposure.

"High End" exposure is the highest dose estimated to be experienced by some individuals, commonly stated as approximately equal to the 90th percentile exposure category for individuals.

Quantifying Exposure. There are three basic approaches for quantifying exposure. Each approach is based on different data, and has different strengths and weaknesses; using the approaches in combination can greatly strengthen the credibility of an exposure risk assessment.

- Point of Contact Measurement
- Scenario Evaluation
- Reconstruction -

Step 4: Risk characterization

Risk characterization is the last step of a human health risk assessment. A risk characterization conveys the risk assessor's judgment as to the nature and presence or absence of risks, along with information about how the risk was assessed, where assumptions and uncertainties still exist, and where policy choices will need to be made. Risk characterization takes place in both human health risk assessments and ecological risk assessments.

2. Ecological Risk Assessment

Even an ecological risk assessment starts with a good plan. Before anything though there is a need to make judgments early when planning major risk assessments regarding the purpose, scope, and technical approaches that will be used. To start, risk assessors will typically ask the following questions:

- 1. Who/What/Where is at risk?
- Individual
- General population
- Lifestages such as juveniles or adults
- Population subgroups highly susceptible (for example, due to genetics) and/or highly exposed (for example, based on geographic area)
- o Different species mink, for example, are highly susceptible to PCBs
- 2. What is the environmental hazard of concern?
- Chemicals (single or multiple/cumulative risk)
- Radiation
- Physical (changes to a habitat)
- o Microbiological or biological (disease or invasive species)
- o Nutritional (for example, fitness or metabolic state)
- 3. Where do these environmental hazards come from?
- Point sources (for example, smoke or water discharge from a factory; contamination from a Superfund site)
- o Non-point sources (for example, automobile exhaust; agricultural runoff)
- Natural
- 4. How does exposure occur?
- Pathways (recognizing that one or more may be involved)
- Air
- Surface Water
- Groundwater
- Soil
- Solid Waste
- Food

Phases of Ecological Risk Assessment

The different phases of the ecological risk assessment process include the problem formulation, analysis, risk characterization and risk management as shown in figure below.

Phase 1: Problem Formulation

sources

The objective of the problem formulation phase is to define an assessment endpoint to determine what ecological entity is important to protect. An ecological entity can be:

- A species (for instance: piping plover)
- A functional group of species (for instance: piscivores i.e., fish eaters)
- A community (for instance: benthic invertebrates)
- An ecosystem (for instance: lake)
- A specific valued habitat (for instance: wet meadows)
- Another entity of concern

Phase 2: Analysis

The objective of the analysis phase is to provide the ingredients necessary for determining or predicting ecological responses to stressors under exposure conditions of interest.


Analysis is the determination of what plants and animals are exposed and to what degree they are exposed and if that level of exposure is likely or not to cause harmful ecological effects. Calculations used may include:

• Hazardquotients

- various parameters
- Areause
- Foodingestionrate
- **Bioaccumulationrates**
- **Bioavailability**
- Life stage

Phase 3: Risk Characterization

The objective of the risk characterization phase is to use the results of analysis to estimate the risk posed to ecological entities. The assessor then describes the risk, indicating the overall degree of confidence in the risk estimates, summarizing uncertainties, citing evidence supporting the risk estimates, and interpreting the adversity of ecological effects.



3.2 Significance Of Environmental Risk Assessment

significance of environmental risk assessment

The risk assessment establishes levels of contaminants that can remain at a site and still be adequately protective of public health. The risk assessment provides a consistent process for evaluating and documenting public health hazards associated with exposure to environmental contamination.

4.0 CASE HISTORIES

4.1 Case History: Environmental Impact Assessment In Nigeria: Regualatory Background And Procedural Framework

(environmental impact assessment in nigeria: regulatory background and procedural framework Nerry echefu and .E. Akpofure, 2002)

As a consequence of the illegal dumping of toxic wastes in Koko, in the former Bendel State, in 1987, the Nigerian Government promulgated the Harmful Wastes Decree which provides the legal framework for the effective control of the disposal of toxic and hazardous waste into any environment within the confines of Nigeria. This was immediately followed by the creation of a regulatory body, the Federal Environmental Protection Agency (FEPA) in 1988. FEPA is charged with the overall responsibility of protecting and developing the Nigerian environment. To put this into action a National Policy on the Environment was developed. This is the main working document for the preservation and protection of the Nigerian environment. States and Local Government Councils were also encouraged to establish their own environmental regulatory bodies for the purpose of maintaining good environmental quality as it applies to their particular terrain. The EIA Decree No. 86 of 1992 is an additional document with the same aim of protecting the Nigerian environment. It is particularly directed at regulating the industrialization process with due regard to the environment. By this Decree, no industrial plan/development/activity falling under the FEPA's mandatory list can be executed without prior consideration of the environmental consequences of such a proposed action, in the form of an environmental impact assessment. The Department of Petroleum Resources (DPR), an arm of the Ministry of Petroleum Resources, recognizing the national importance of the oil and gas industry sector to the continued growth of the Nigerian economy and realizing that the continued

exploitation, exploration and production of the oil resources has serious environmental impacts, also decided to set out comprehensive standards and guidelines to direct the execution of projects with proper consideration for the environment.

There is duplication of functions and overlapping responsibilities in the processes and procedures guiding the execution of the various impact assessment tasks. Consequently, serious bottlenecks and bureaucratic confusion are created in the process. The result is a waste of resources, financially and materially. This paper examines the statutory regulatory framework for the EIA process, and the inadequacies and misinterpretations of the various statutes, which have often led to delays in the execution of EIAs in Nigeria. An attempt will be made to streamline these various responsibilities through a reorganization of the regulatory environmental framework. This way, it is hoped that the bottlenecks and wastage of resources will be eliminated.

INSTITUTIONAL AND REGULATORY FRAMEWORK

Prior to the establishment of the FEPA there were sectoral environmental regulations with various significant responsibilities relating to environmental protection and improvement. Also in existence were commissions with advisory capacity in environmental matters and environmental NGOs. Due to various activities and the complex combination of interdependent operations of the oil industry it, more than any other sector, adversely affects the environment. In the oil industry DPR adopted remedial, though inadequate, enforcement tools which included compliance monitoring and the issuing of permits/licences. Studies indicated the extent of devastation the oil industry has caused to aquatic and terrestrial ecosystems and cultural and historical resources. This, coupled with the community's dissatisfaction and agitation, especially in the Ogoni and Ijaw homelands, reinforced the need for the sector to plan, protect and enhance prudently the environmental resources for a better environment, the need to control new installations or projects with capacity to degrade the environment was also identified. This compelled DPR to issue updated Environmental Guidelines and Standards (EGAS) in 1991 providing for the first time, together with pollution abatement technology, guidelines and standards and monitoring procedures, a mandatory EIA report as enforcement tool. There are other regulatory bodies within the sector. FEPA, charged with the protection and development of the environment, prepared a comprehensive national policy, including procedures for environmental impact assessment for, amongst others, all development projects. Enforcement powers were also prescribed. In the National Policy on the Environment (NPE), FEPA adopted a strategy that guarantees an integrated holistic and systemic view of environmental issues that leads to prior environmental assessment of proposed activities. The other regulators including State EPAs (unnecessarily charged with similar and identical responsibilities to those of FEPA) rather than cooperating with FEDA undermine its efforts as they demand a role in the state of the environment within their areas. This occurs particularly where FEPA involves them only at the review stage in the EIA process. This creates a lot of confusion and bureaucratic delays in implementing the EIA process leading to enormous cost and unnecessary waste of time.

ENVIRONMENTAL IMPACT ASSESSMENT SYSTEM

Features The principal legislation is Decree 86 of 1992 which made EIA mandatory for both public and private sectors for all development projects. It has three goals and thirteen principles

for how these are to be achieved. The goals are: • Before any person or authority takes a decision to undertake or authorize the undertaking of any activity that may likely or significantly affect the environment, prior consideration of its environmental effects should first be taken. • To promote the implementation of appropriate procedures to realize the above goal. • To seek the encouragement of the development of reciprocal procedures for notification, information exchange and consultation in activities likely to have significant trans-state (boundary) environmental effects. FEPA categorizes mandatory study activities into three categories. (see Figure 1 below): Category 3 activities have beneficial impacts on the environment. For Category 2 activities (unless within the Environmentally Sensitive Area) full EIA is not mandatory, while Category 1 activities require full and mandatory EIA. Either listing or an initial environmental evaluation (IEE) system is used to determine projects requiring full EIA

PROCESS AND PROCEDURAL FRAMEWORK

The EIA process is the various stages a project undergoes from proposal to approval for implementation, resulting in the issuing of an Environmental Impact Statement (EIS) and certificate. The term encompasses several stages, viz: • determining if FEPA environmental laws/regulations have been triggered; • screening a project for potential environmental effects; • scoping to determine the spatial and temporary dimension of environmental effects; • carrying out detailed base line studies to determine the environmental condition prior to project implementation; • preparing a detailed assessment report; • carrying out a panel review of the EIA report if this is necessary; and • obtaining authorization/approval, where appropriate. For FEPA, the Director General/Chief Executive is the responsible officer. The National Procedural Guidelines show practical steps from project conception to commissioning (see Figure 2). The steps are: • project proposal • initial environmental examination (IEE)/preliminary assessment • screening • scoping • EIA study • review • decision making • monitoring, and • auditing. The proponent initiates the process in writing to the responsible officer. A notification form is duly completed with all relevant information on the proposal. Using the criteria of : • magnitude probable severity of each potential impact; • prevalence/extent and scope - extent to which the impact may eventually extend; • duration and frequency - is activity short term, long term or intermittent; • risks - probability of serious environmental effects; • significance/importance value attached to a specified area; and • mitigation - measures available for associated and potential environmental effects FEPA does internal screening (IEE) to determine the project's category under the mandatory study activities list. Where no adverse environmental effects exist, the EIA is issued and the project commences with appropriate mitigation and monitoring measures. Otherwise within ten working days of receipt of the proposal, the screening report is sent to the proponent for scoping and the preparation of Terms of Reference (ToR). The ToR embodies the scope of the proposed EIA study and this is examined and the scope of the study defined accordingly by FEPA. The proponent carries out the study, generally using consultants, and the draft EIA report in 15 copies is submitted to the responsible officer. For this draft report to be complete it must as an annex record the results of public participation in a public form. Within 15 working days of the receipt of the draft report, FEPA concludes evaluation of the draft and determination of the review method which it communicates to the proponent in writing. The four methods are: • In-house review. • Panel review (sitting may be public). • Public review - an elaborate display of the report for 21 working days with appropriate display venues chosen by FEPA for the convenience of the public stakeholders and communities. Through newspaper advertisement FEPA invites interested groups /persons to participate. • Mediation. Within one month of the review process, review comments are furnished to the proponent. In this review stage, the public participates only when FEPA's chosen method of review guarantees its participation. The final EIA report, addressing and proffering answers to review comments, is submitted within six months to the responsible officer. At this early stage, and on mutual agreement, FEPA and the proponent seconditions establishing a follow-up program (mitigation, compliance and monitoring plan), a monitoring strategy and audit procedure.

4.2 CASE HISTORY: Environmental risk assessment in selected dumpsites in Abakaliki metropolis, Ebonyi state, southeastern Nigeria

(Daniel Aja et al 2021 environmental risk assessment in selected dumpsites in abakiliki metropolis, ebonyi state southeasthern Nigeria)

Presently, the magnitude of soil pollution at global scale is increasing significantly due to rapid rate of industrialization, increase in population growth and urbanization (UNIDO, 2011). Accordingly, the increment in waste load has led to environmental pollution and degradation in many cities of the world. Most African countries including Nigeria are dumping ground for electronic and other hazardous wastes containing lead, cadmium, mercury, cobalt, arsenic and other toxic metals. These metals in the soil affect the health of living organisms and natural environment (Zurbrug, 2003; Amadi et al., 2010; Okolo et al., 2013a) especially when the concentrations are above certain threshold (Udeigwe et al., 2015). Furthermore, small and largescale industries located in urban areas often dispose their wastes along with municipal solid wastes, which is a serious threat to the entire ecosystem (Dongballe, 2016).

Potential contamination of soil by heavy metal may occur as a result of leaching from industrial processes and other anthropogenic activities including indiscriminate disposal of e-wastes, animal manure or sewage to the soil, waste-water excessive application of fertilizer and and petrochemical spillage (Khan et al., irrigation, atmospheric deposition, crude oil 2008; Zhang et al., 2010; Okolo et al., 2013a). Metal buildup in soils and sediments has serious environmental risks because of its harmful effect to both terrestrial (Tang et al., 2014) and aquatic ecosystem, including the underground aquifer (Igwe and Chukwura, 2018). However, the availability of heavy metals for plant uptake in the soil depends on soil pH, clay content and organic matter amongst other factors (Molla and Huq, 2002, 2004). Anions such as nitrate (NO₃⁻), sulphate (SO₄²⁻) and phosphate (PO₄³⁻) are important sources of nutrients for plant growth and are required for synthesis of different compounds essential for all living organisms (Chinyere et al., 2013), but can be inhibited by the presence of heavy metals in the soil.

The study area

This study was conducted in Abakaliki Metropolis, Ebonyi state, South-eastern Nigeria. The area lies within Latitude 06°04'N and Longitude 08° 65'E in the derived savannah zone of South-East Nigeria. Three dumpsites were used for the study: New layout dumpsite (NLD) 6° 19' 42.66" N,

8° 06' 55. 78" E; Azuiyiokwu dumpsite (AD) 6° 18' 44.90" N, 8° 05' 55.26" E; and Mechanic village dumpsite (MVD) 6° 18' 58.62 N, 8° 07' 42.52" E (Fig. 1).

Abakaliki has a land area of about 5670 square kilometers with an estimated population of 141, 438 (NPC, 2006). The inhabitants of Abakaliki predominantly lead agrarian life and generate mainly household wastes with a mixture of e-wastes. The area is associated with relatively high temperature range (27 °C-31 °C). The rainfall pattern is bimodal (April–July) and (September–November) with an August break (Mbah et al., 2017). The relative humidity range is 60–80% for minimum and maximum. The soil of the area is dominated by Nitisols (NT) (Fig. 2) which represents the hydrological soil group "C" and it is described as Silt Loam or Sandy Clay Loam with high relative run-off potential (Aja et al., 2019).

Soil sampling

Soil sampling was carried out during the dry season of 2019 (between October and December). The sampling points (Mechanic Village Dumpsite (MVD), Azuiyiokwu Dumpsite (AD) and New-layout Dumpsite (NLD)) were cleared of waste before sample collection. Soil samples were collected at 0–15 cm and 15–30 cm soil depth in each dumpsite. A total of thirty-six (36) samples were collected using handheld auger. The soil samples were arranged separately according to the method of Hodgson (1993). Auger samples were air dried, crushed, sieved with 2 mm sieve, and transported to the Lagos State Environmental protection Agency (LASEPA) Laboratory for analysis in black polyethylene bags.

Determination of heavy metals and anions

Heavy metals were determined by the Aqua Regia method as modified by Salt (1998). Air- dried and previously sieved soil samples were weighed to obtain 0.5 g and this quantity was digested with concentrated nitric acid (HNO₃) and filtered through ash-less filter paper. The clear digest was diluted in a 50 ml acid cleaned standard flask with distilled water up to the required mark. Atomic Absorption Spectrometer (AAS) (Shimadzu double beam AA-6300 and Perkin Elmer Aanalyst 400) was used to analyze the amount of lead (Pb), cadmium (Cd), Copper (Cu), Zinc (Zn) and Iron (Fe) in the sample solutions.

For sulphate and nitrate, 10 g of the soil sample was weighed into a 50 ml centrifuge tube and 25 ml of distilled water was added. The solution was stirred occasionally for 30 min with a glass rod on an orbital shaker. The solution was filtered using filter paper. Pilos of sulphate and nitrate were added to the clear filtrate. The samples were then taken to spectrophotometer for detection and reading. For phosphate (PO_4^{3-}), the method used was the same as the one described above for sulphate and nitrate. However, 10 ml of distilled water was added and phosphate pilos were added in contrast to what was added for sulphate and nitrates.

Contamination levels assessment

Several contamination indicators such as factor of contamination (C_f), factor of enrichment (E_f), geo-accumulation index (I_{geo}), environmental risk index (R_i) and modified environmental risk index (MR_i) as described by Keshavarzi and Kumar (2020); and Kumar et al. (2018) were used

to evaluate the degree of pollution and the level of environmental risks posed by heavy metals leaching in the selected dumpsites.

2.5.1. Contamination factor (C_f)

The contamination factor indicates the artificial inputs of heavy metals in the dumpsite (Ahmed et al., 2016). It is given by the following equation:(1)Cf=HMsHMcWhere,

 HM_s is the concentrations of heavy metals in sampling sites and HM_c is the concentrations of heavy metals in reference. The contamination factor (C_f) is categorized into four viz: low contamination $(C_f < 1)$; moderate contamination $(1 < C_f \le 3)$; high contamination $(3 < C_f \le 6)$ and very high contamination $(C_f > 6)$ (Hakanson, 1980). The global mean concentrations of metals in the soil as reported by Turekian and Wedepohl (1961) were used as control in this study because country specific background measurements for these elements are not available.

Environmental risk assessment (RI and MRI)

The environmental risk index (R_I) was computed to estimate the potential environmental risk of heavy metals from the dumpsites. The index is given by the product of the contamination factor (C_f) of each metal and the toxicological response factor (Tr) of individual metal (Kumar et al., 2018). It is expressed by the following equation:(4)RI=CFn×TrWhere

 CF_n and T_r are the contamination factor and toxicological response for individual metal. The toxicological response (Tr) has a value of 1 for Zn; 5 for Pb and Cu; 30 for Cd (Manoj and Padhy, 2014). Environmental risk index (R_I) is categorized into five groups viz: low risk (R_I < 30), moderate risk (R_I: 30–60), considerable risk (R_I: 60–120), high risk (R_I: 120–240), significantly high risk (R_I > 240).

To compute the modified ecological risks index (MR_I) which is essentially as a result of anthropogenic additions of metals in dumpsites, the factor of contamination (C_f) is replaced by factor of enrichment (E_f) in Eq. (4) above (Kumar et al., 2018).(5)MRI=Efn×TrWhere:

 E_{fn} and T_r are the factor of enrichment and toxicological response of individual heavy metals. The ranking for risk assessment is as follows: low risk (MR_I < 40), moderate risk (40–80), considerable risk (80–160), high risk (160–320), and very high risk (>320).

Results

Descriptive statistics of heavy metals and anions

Tables 1 and 2 showed the results of heavy metal concentration across the three dumpsites. The concentrations of Pb ranged from 12.90 to 19.51 mgkg^{-1} at 0-15 cm depth. The highest concentration (19.51 mgkg⁻¹) of Pb was recorded at MVD and the lowest concentration (12.90 mgkg⁻¹) was found NLD. The concentration of lead at AD was found to be 18.72 mgkg⁻¹. Concentrations of Cd ranged from 0.01 to 0.14 mgkg⁻¹ in 0–15 cm soil depth. Azuiyiokwu dumpsite had the highest concentration (0.14 mgkg⁻¹) followed by MVD which had 0.10 mgkg⁻¹ (Tables 1 and 2). The least concentration was found at NLD (0.01 mgkg⁻¹). The sub-soil (15–30 cm) concentrations of Cd ranged from 0.03 to 0.12 mgkg⁻¹. The lowest concentration was obtained at MVD (0.03 mgkg⁻¹).

| 0-15 cm depth. | | | | | | | | |
|---|---------|------|--------|--------|-----------|-------------------|------------------------------|-------------------|
| Sites | Pb | Cd | Cu | Zn | Fe | PO4 ³⁻ | NO ₃ ⁻ | SO4 ²⁻ |
| MVD | 19.51 | 0.10 | 56.26 | 84.21 | 280.16 | 0.10 | 11.90 | 4.00 |
| AD | 18.72 | 0.14 | 16.41 | 42.21 | 84.13 | 2.31 | 2.70 | 29.01 |
| NLD | 12.90 | 0.11 | 10.35 | 63.96 | 26.42 | 0.55 | 16.30 | 4.90 |
| Mean | 17.04 | 0.12 | 27.67 | 63.46 | 130.24 | 0.99 | 10.30 | 12.64 |
| Std Deviation | 3.61 | 0.02 | 24.94 | 21.00 | 133.01 | 1.17 | 6.94 | 14.19 |
| Sample Variance | 13.03 | 0.00 | 622.08 | 441.19 | 17,690.37 | 1.36 | 48.16 | 201.27 |
| Skewness | -1.64 | 1.29 | 1.62 | -0.11 | 1.37 | 1.45 | -0.98 | 1.72 |
| Range | 6.61 | 0.04 | 45.91 | 42.00 | 253.74 | 2.21 | 13.60 | 25.01 |
| Minimum | 12.90 | 0.10 | 10.35 | 42.21 | 26.42 | 0.10 | 2.70 | 4.00 |
| Maximum | 19.51 | 0.14 | 56.26 | 84.21 | 280.16 | 2.31 | 16.30 | 29.01 |
| Sum | 51.13 | 0.35 | 83.02 | 190.38 | 390.71 | 2.96 | 30.90 | 37.91 |
| Count | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| MVD: Mechanic Village Dum AD: Azuiyiokwu dumpsite. | npsite. | | | | | | | |

Table 1. Descriptive Statistics of Heavy Metals and Anion Concentrations (mgkg^{-1}) at 0–15 cm denth

NLD: New Layout Dumpsite.

Table 2. Descriptive Statistics of Heavy Metals and Anion Concentrations $(mgkg^{-1})$ at 15–30 cm depth

| Sites | Pb | Cd | Cu | Zn | Fe | PO4 ³⁻ | NO ₃ ⁻ | SO4 ²⁻ | |
|-------|------|------|-------|------|--------|-------------------|------------------------------|-------------------|--|
| MVD | 4.71 | 0.03 | 21.31 | 11.2 | 250.36 | 2.72 | 12.3 | 9 | |

IIARD – International Institute of Academic Research and Development

Page **43**

| Sites | Pb | Cd | Cu | Zn | Fe | PO4 ³⁻ | NO ₃ ⁻ | SO4 ²⁻ |
|-----------------|-------|------|--------|--------|-----------|-------------------|------------------------------|-------------------|
| AD | 9.53 | 0.12 | 1.38 | 45.38 | 20.11 | 2.39 | 1.5 | 39 |
| NLD | 4.40 | 0.05 | 2.18 | 10.32 | 12.18 | 0.59 | 20.3 | 58 |
| Mean | 6.21 | 0.07 | 8.29 | 22.30 | 94.22 | 1.90 | 11.37 | 35.33 |
| Std Deviation | 2.88 | 0.05 | 11.28 | 19.99 | 135.28 | 1.15 | 9.43 | 24.70 |
| Sample Variance | 8.28 | 0.00 | 127.30 | 399.71 | 18,301.28 | 1.31 | 89.01 | 610.33 |
| Skewness | 1.71 | 1.39 | 1.72 | 1.73 | 1.73 | -1.57 | -0.44 | -0.65 |
| Range | 5.13 | 0.09 | 19.93 | 35.06 | 238.18 | 2.13 | 18.80 | 49.00 |
| Minimum | 4.40 | 0.03 | 1.38 | 10.32 | 12.18 | 0.59 | 1.50 | 9.00 |
| Maximum | 9.53 | 0.12 | 21.31 | 45.38 | 250.36 | 2.72 | 20.30 | 58.00 |
| Sum | 18.64 | 0.20 | 24.87 | 66.90 | 282.65 | 5.70 | 34.10 | 106.00 |
| Count | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |

IIARD International Journal of Geography & Environmental Management (IJGEM) Vol. 9 No. 2 2023 E-ISSN 2504-8821 P-ISSN 2695-1878 www.iiardjournals.org

MVD: Mechanic Village Dumpsite.

AD: Azuiyiokwu dumpsite.

NLD: New Layout Dumpsite.

Tables 1 and 2 showed that the concentration of Cu ranged from 10.35 to 56.26 $mgkg^{-1}$ in the surface (0-15 cm) soil samples. The highest concentration of 56.26 mgkg⁻¹ was obtained at the MVD. The concentration of Cu obtained at AD was 16.41 mgkg⁻¹. At the depth of 15–30 cm, the concentrations of Cu across the dumpsites ranged from 1.38 to 21.31 mgkg⁻¹. MVD again had concentration $(21.31 \text{ mgkg}^{-1})$. The concentration of Zn the highest as presented in Tables 1 and 2 showed that surface (0-15 cm) soil samples had the highest Zn concentration compared to the subsoil (15-30 cm) samples. The concentrations of Zn in surface soil ranged from 21.32 to 84.21 mgkg⁻¹. The highest concentration of Zn (84.21 mgkg⁻¹) was found at MVD while the lowest concentration of 21.32 mgkg⁻¹ was obtained at NLD. Within 15–30 cm depth,

the concentration of Zn ranged from 10.32 to 45.38 mgkg^{-1} which is lower than the topsoil Zn concentration (21.32–84.21 mgkg⁻¹).

Tables 1 and 2 indicated that Fe had the highest concentrations in all the three dumpsites. The topsoil (0-15 cm) had the highest concentrations of Fe compared to the sub-soil (15-30 cm). The concentration of Fe in the topsoil (0-15 cm) ranged from 26.42 to 280.16 mgkg⁻¹ across the Mechanic village dumpsite had the highest Fe concentration dumpsites. of 280.16mgkg⁻¹ followed by AD (84.13mgkg⁻¹) and NLD with the lowest concentration of 26.42 mgkg⁻¹. At 15–30 cm depth, the concentrations of Fe ranged from 12.18 to 250.36 mgkg⁻¹. Mechanic village dumpsite again had the highest concentration (250.36 mgkg⁻¹) followed by AD that had 84.13 mgkg⁻¹. The lowest concentration was obtained at NLD (12.18 mgkg⁻¹). The concentration of phosphate (PO_4^{3-}) obtained at AD within the depth of 0–15 cm was 2.3 mgkg⁻¹ (Table 2; Fig. 3). Mechanic village dumpsite had 0.1 mgkg⁻¹ while NLD had 0.55 mgkg^{-1} within the depth of 0-15 cm. At the depth of 15-30 cm, the amount of PO_4^{3-} obtained at AD was 2.39 mgkg⁻¹ while NLD and MVD had 0.59 mgkg⁻¹ and 2.72 mgkg⁻¹, respectively. Our result showed that Nitrate (NO_3^-) and Sulphate (SO_4^{2-}) followed the same

trend with that of PO_4^{3-} across the three dumpsites investigated.

Contamination levels assessment

The contamination level assessment was done by implementing Eqs. (1)–(5) and the results are presented in Tables 5–7 below.

| Heavy metal | C _f | $\mathbf{E_{f}}$ | Igeo | RI | MRI |
|-------------|--------------------|------------------|--------------------|-----|------|
| Pb | 4.71 | 1880 | 0.80 | 22 | 9400 |
| Cd | 0.60 | 20 | 0.12 | 18 | 600 |
| Cu | 2.03 | 850 | 0.43 | 10 | 4250 |
| Zn | 0.2 | 90 | 0.05 | 0.2 | 90 |
| Fe | 2×10^{-5} | 1 | 2×10^{-3} | _ | _ |

Table 5. Contamination level assessment at Mechanic village dumpsite.

Table 6. Contamination level assessment at Azuiyiokwu dumpsite.

| Heavy metal | C _f | $\mathbf{E_{f}}$ | Igeo | RI | MRI |
|-------------|----------------|------------------|------|----|--------|
| Рb | 9.5 | 3800 | 1.91 | 48 | 19,000 |
| Cd | 2.4 | 800 | 0.48 | 72 | 24,000 |

IIARD – International Institute of Academic Research and Development

Page **45**

| IIARD International Journal of Geograp | phy & Environmental Management (IJGEM) |
|--|--|
| Vol. 9 No. 2 2023 E-ISSN 2504-8821 | P-ISSN 2695-1878 www.iiardjournals.org |

| Heavy metal | C _f | E _f | Igeo | RI | MRI |
|-------------|--------------------|----------------|--------------------|-----|-----|
| Cu | 0.14 | 55 | 0.03 | 0.7 | 275 |
| Zn | 0.9 | 362 | 0.18 | 0.9 | 362 |
| Fn | 2×10^{-5} | 1 | 4×10^{-5} | _ | _ |

Table 7. Contamination level assessment at New-layout dumpsite.

| Heavy metal | C _f | E _f | Igeo | RI | MRI |
|-------------|--------------------|----------------|--------------------|-----|--------|
| Pb | 4.4 | 176 | 0.90 | 22 | 880 |
| Cd | 1 | 400 | 0.70 | 30 | 12,000 |
| Cu | 0.2 | 22 | 0.04 | 1 | 110 |
| Zn | 0.2 | 82 | 0.04 | 0.2 | 82 |
| Fe | 1×10^{-5} | 1 | 5×10^{-4} | _ | _ |

Discussion

Descriptive statistics

The results of metal concentrations in sub-soil (15-30 cm) samples across the studied dumpsites indicated that the concentrations of lead (Pb) were 4.40 mgkg⁻¹, 4.71 mgkg⁻¹ and 9.53 mgkg⁻¹ for NLD, MVD and AD, respectively. The Lagos state Environmental protection Agency (LASEPA, 2005) and the world Health organization (WHO, 2006) soil quality guideline for Pb is 5.0 mgkg⁻¹. Elevated concentration of Pb was noticed in all the surface soil samples. However, the concentration of Pb in the sub-soil was found to be within the acceptable limits except for AD that had 9.5 mgkg⁻¹. This agrees with the result of Esakku et al. (2014) which showed higher concentrations of Pb within 1–2 m depth in various dumpsites in India. Okolo et al. (2013b) and Olowookere et al. (2018) reported similar trend in different parts of Nigeria.

The concentrations of Cd found at AD and MVD at 0-15 cm were 14 and 10 times higher than the WHO permissible limit (0.01 mgkg⁻¹) while Cd concentration found at NLD was within the

permissible limit. The sub-soil (15-30 cm) concentrations of Cd ranged from 0.03 to 0.12 mgkg⁻¹. The lowest concentration was obtained at MVD (0.03 mgkg^{-1}) and is 3 times higher than the WHO permissible limit while the highest concentration (0.12 mgkg^{-1}) was found at AD and it's 12 times higher than the WHO permissible limit. These values were above the recommended concentrations limit of 0.01 mgkg⁻¹ by World Health organization (WHO, 2006) but below the recommended limit by the Lagos State Environmental Protection Agency (0.2 mgkg^{-1}) (LASEPA, 2005). This implies that cadmium concentrations were within the acceptable limits across the studied dumpsite with regards to LASEPA (2005) standard. Similarly, the concentrations of arsenic, mercury and cadmium found by Esakku et al. (2014) at various dumpsites in India were comparatively less than that obtained for the other metals. Nevertheless, even though the concentrations of Cd at NLD is within the WHO and LASEPA permissible limits, it should be noted that heavy metal contamination even if in traces or small quantities are serious environmental concern as these metals can be readily transported and with high chances of persisting within the ecosystem for a long period of time thereby increasing their concentrations over time (Okolo et al., 2018).

The highest concentration $(10.35 \text{ mgkg}^{-1})$ of Cu was found at NLD. The concentrations of Cu found at MVD, AD and NLD at 0–15 cm were 1.8, 6.0 and 9.6 times lower than the WHO permissible limit (100 mgkg^{-1}) , respectively. The Cu concentration at NLD was found to be 2.18 mgkg⁻¹ while the least concentration of 1.38 mgkg⁻¹ was found at AD. The concentrations of Cu recorded at MVD at 15–30 cm (21.31 mgkg⁻¹) was about 5 times lower than WHO permissible limit while the concentrations found at AD and NLD at 15–30 cm were 72 and 46 times lower than the WHO permissible limit (100 mgkg⁻¹), respectively. Considering the established guidelines, toxic levels were not observed for Cu at MVD, AD and NLD within the depth of 0–30 cm. The elevated concentration of heavy metals at the topsoil (0 –15 cm) relative to the sub soil (15–30 cm) is in line with the observations of Pan et al. (2010), Okolo et al. (2013a), (2015) and Olowookere et al. (2018).

The highest concentration of Zn $(84.21 \text{ mgkg}^{-1})$ was found at MVD while the lowest concentration of 21.32 mgkg^{-1} was obtained at NLD. The concentration of Zn observed at AD was 48.21 mgkg^{-1} . In most cases, high Zn concentration tends to reduce Cu concentration (Allen, 1995) as evidenced in our study (Tables 1 and 2). In the topsoil across all dumpsites, Zn concentration increases while Cu concentration reduces.

Contamination levels and ecological risks assessment

Heavy metals loading and their ecological risks across the dumpsites were assessed using several pollution indices such as factor of contamination (C_f), factor of enrichment (E_f), geo-accumulation index (I_{geo}), environmental risk index (R_I) and modified environmental risk index (MR_I). Our result show moderate to high contamination of Cd, Cu and Pb across the studied dumpsites. We observed low enrichment of Fe across the dumpsites, high enrichment of Cu at New-layout dumpsite and exceptionally high enrichment of Pb, Cd, and Zn across the 3 dumpsites. Index of geo-accumulation indicates moderate pollution across the dumpsites except for Azuiyiokwu dumpsite where Pb appears to have high pollution index. There is low environmental risk index (RI) at Mechanic village dumpsite and New-layout dumpsite while Azuiyiokwu dumpsite recorded a moderate to considerable risk. The modified environmental risk index (MRI) showed very high risk across the studied dumpsites.

5.0 Conclusion

Environmental risk assessment and environmental impact assessment have broad definitions and significance. It has been defined and explained differently by many authors. But in all it involves the process of assessing project or health risk associated with human activities and natural hazards in the environment. Risk assessment are expected to be carried out before a project is executed, and risk assessment should be done to control health problems associated with heavy metal and hazardous chemical waste in the environment.

REFERENCES

- "Databases on toxicology, hazardous chemicals, environmental health, and toxic releases". TOXNET. NLM. May 2012. Retrieved 9 June 2013.
- "Household Products Database". U.S. Dept. of Health & Human Services. January 2013. Retrieved 9 June 2013.
- "Principle of Environmental Impact Assessment Best Practice" (PDF). International Association for Impact Assessment. 1999. Archived from the original (PDF) on May 5, 2012. Retrieved September 15, 2020
- "Risk Assessment and Regulation Information from the NLM". National Library of Medicine. Retrieved 9 June 2013.
- "Risk Assessment Portal". EPA. 13 May 2013. Retrieved 9 June 2013.
- "Risk Assessment". www.epa.gov. US Environmental Protection Agency. 2013-09-26. Retrieved 2016-04-07.
- Caves, R. W. (2004). Encyclopedia of the City. Routledge. p. 227.
- Commoner B. "Comparing apples to oranges: Risk of cost/benefit analysis". In Iannone AP (ed.). Contemporary moral controversies in technology. pp. 64–65.
- Eccleston, Charles H. (2011). Environmental Impact Assessment: A Guide to Best Professional Practices. Chapter 5. ISBN 978-1439828731

- EPA Alumni Association: Senior EPA officials discuss early implementation of the Safe Drinking Water Act of 1974, Video, Transcript (see pages 11,14).
- Hoffmann TC, Del Mar C (February 2015). "Patients' expectations of the benefits and harms of treatments, screening, and tests: a systematic review" (PDF). JAMA Internal Medicine. 175 (2): 274–86. doi:10.1001/jamainternmed.2014.6016. PMID 25531451.
- Holder, J., (2004), Environmental Assessment: The Regulation of Decision Making, Oxford University Press, New York; For a comparative discussion of the elements of various domestic EIA systems, see Christopher Wood Environmental Impact Assessment: A Comparative Review (2 ed, Prentice Hall, Harlow, 2002).
- Holzmann R, Jørgensen S (2001). "Social Risk Management: A New Conceptual Framework for Social Protection, and Beyond". International Tax and Public Finance. 8 (4): 529– 56. doi:10.1023/A:1011247814590. S2CID 14180040.
- Kasperson RE, Renn O, Slovic P, Brown HS, Emel J, Goble R, Kasperson JX, Ratick S (1988). "The social amplification of risk: A conceptual framework" (PDF). Risk Analysis. 8 (2): 177–187. doi:10.1111/j.1539-6924.1988.tb01168.x.
- Levi R (1 June 2018). "Getting Real About Both Benefits and Risks". Science & Practice, English Special 2018. Swedish Agency of Health Technology Assessment and Assessment of Social Services. ISSN 1104-1250. Retrieved 2018-06-14.
- Lock G (June 2017). Phillips M (ed.). "Public Safety Diving-Dynamic Risk Assessment" (PDF). PS Diver Magazine (116): 9. Retrieved 20 June 2017.
- MacKinnon, A. J., Duinker, P. N., Walker, T. R. (2018). The Application of Science in Environmental Impact Assessment. Routledge.

- Mandelbrot B, Hudson RL (2008). The (mis)Behaviour of Markets: A Fractal View of Risk, Ruin and Reward. London: Profile Books. ISBN 9781846682629.
- Manuele FA (2016). "Chapter 1: Risk Assessments: Their Significance and the Role of the Safety Professional". In Popov G, Lyon BK, Hollcraft B (eds.). Risk Assessment: A Practical Guide to Assessing Operational Risks. John Wiley & Sons. pp. 1– 22. ISBN 9781118911044.
- Nakaš N (21 November 2017). "Three Lessons About Risk Management from Everyday Life". Knowledge Hub. Center of Excellence in Finance. Retrieved 19 July 2018.
- Nielsen GH, Heiger-Bernays WJ, Levy JI, White RF, Axelrad DA, Lam J, et al. (January 2023). "Application of probabilistic methods to address variability and uncertainty in estimating risks for non-cancer health effects". Environmental Health. 21 (Suppl 1): 129. doi:10.1186/s12940-022-00918-z. PMC 9835218. PMID 36635712.
- O'Brien M (2002). Making better environmental decisions: an alternative to risk assessment. Cambridge, Massachusetts: MIT Press. ISBN 0-262-65053-3. Retrieved 27 September 2010.
- Rausand M (2013). "Chapter 1: Introduction". Risk Assessment: Theory, Methods, and Applications. John Wiley & Sons. pp. 1–28. ISBN 9780470637647
- Rausand M (2013). "Chapter 6: Accident Models". Risk Assessment: Theory, Methods, and Applications. John Wiley & Sons. pp. 137–76. ISBN 9780470637647.
- Shirey R (August 2007). "Internet Security Glossary, Version 2". Network Working Group. The IETF Trust. p. 9. Retrieved 19 July 2018.
- Shrader-Frechette K, Westra L (October 1997). Technology and Values. Lanham, Md.: Rowman & Littlefield Publishers. ISBN 978-1-4616-4399-9

IIARD – International Institute of Academic Research and Development

- Stacey D, Légaré F, Lewis K, Barry MJ, Bennett CL, Eden KB, et al. (April 2017). "Decision aids for people facing health treatment or screening decisions". The Cochrane Database of Systematic Reviews. 2017 (4): CD001431. doi:10.1002/14651858.CD001431.pub5. PMC 6478132. PMID 28402085.
- Szabo DT. Loccisano AE (March 30, 2012). "POPs and Human Health Risk Assessment". Dioxins and Persistent Organic Pollutants (3rd ed.). pp. 579-618. doi:10.1002/9781118184141.ch19. ISBN 9781118184141.
- Taleb NN (September 2008). The fourth quadrant: a map of the limits of statistics (PDF). An Edge original essay (Report).
- Vamanu BI, Gheorghe AV, Kaina PF (2016). Critical Infrastructures: Risk and Vulnerability Assessment in Transportation of Dangerous Goods: Transportation by Road and Rail. Springer. p. 11. ISBN 9783319309316.
- Varshavsky JR, Rayasam SD, Sass JB, Axelrad DA, Cranor CF, Hattis D, et al. (January 2023). "Current practice and recommendations for advancing how human variability and susceptibility are considered in chemical risk assessment". Environmental Health. 21 (Suppl 1): 133. doi:10.1186/s12940-022-00940-1. PMC 9835253. PMID 36635753